

28-JAN-2004 Notification received of label changes. See below for these changes.

06-JUL-1998

Our Best

MATCHLESS (R)

BOAT &  
YACHT  
COATING

340 PREMIUM 3.78 L

Antifouling Red

DOMESTIC

CAUTION  
FLAMMABLE

DANGER  
POISON

IMPORTANT: READ THE LABEL BEFORE USING. FOR USE ON BOATS ONLY.  
SKIN AND EYE IRRITANT. NOT FOR SPRAY USE. ONLY BRUSH OR ROLLER  
APPLICATION.

GUARANTEE:  
CUPROUS OXIDE 36%  
COPPER AS ELEMENTAL 30%

REGISTRATION NO. 22573  
PEST CONTROL PRODUCTS ACT

MATCHLESS INC.,  
~~P.O. BOX 6090,~~  
~~ST. JOHN'S, NEWFOUNDLAND~~  
~~A1C 5X8~~

Notification Change

LAURENTIDE ATLANTIQUE LTEE  
9322 MAIN STREET, PO BOX 368  
RICHIBUCTO, NB E4W 4C7

SURFACE PREPARATION:

STEEL SURFACES: Must be clean, dry and free of rust. New steel - apply Matchless 362 Epoxy Primer anticorrosive barrier system, followed by two coats of Antifouling. Previously painted surfaces should be wire brushed, scraped or sand blasted and the exposed steel immediately primed with 362 Epoxy Primer before finishing with Antifouling.

WOOD (NEW): Must be clean and dry. Apply one coat of Antifouling let dry for 24 hours, sand lightly, remove dust and apply two coats of Antifouling. Previously Painted Wood Surfaces: Old antifouling paint should be thoroughly sanded and scraped to bare wood then primed and finished using Antifouling.

FIBREGLASS: Wash the fibreglass with Matchless 350 Cleaner and follow with a thorough cleaning of the surface with Matchless 361 Thinner to remove all wax contaminants, change cloths frequently during this procedure. Sand thoroughly to dull the surface. Remove all sanding dust with 361 Thinner and apply two coats of Antifouling: Blistering Gelcoat (Fibreglass): Remove all old antifouling by sanding. Sand all the gelcoat and fill voids with an epoxy fairing compound. Sand areas smooth. Apply two coats of 362 Epoxy Sealer. Apply two coats of Antifouling.

UNDERWATER METAL PARTS AND LEAD KEELS: Scrape, sandblast or wire brush surface to remove old paint and rust. Wash surface with 361 Thinner to remove dust and other residue. Apply two coats of 362 Epoxy Primer. Apply two coats of Antifouling.

Do not use this product on aluminum hulls and outdrives. For best performance apply two coats.

Contact your Matchless representative for detailed surface preparations and recommendations and specifications for use of this Matchless anticorrosive barrier system.

APPLICATION: Mix well. Apply by brush or roller at a temperature between 10 deg C - 30 deg C.

THINNING: If required for application use up to 10% by volume of 360 Thinner. Clean up: Use Matchless 360 Thinner. Coverage: 28 to 32 m<sup>2</sup>/ 3.78 L. Drying Time: Allow 4 hours between coats. IMMERSION: Minimum time 12 hours. Recommended time 24 hours. Maximum time 60 days.

Notice to User

This control product is to be used only in accordance with the directions on this label. It is an offence under the PEST CONTROL PRODUCTS ACT to use a control product under unsafe conditions.

**PRECAUTION:** Keep away from heat, sparks and flame. Vapours from this product are heavier than air and may cause health and explosion hazards. Keep containers tightly closed when not in use. Avoid contact with eyes, skin and clothing. Do not breathe vapours. Wear chemical resistant clothing, with head covering or hat, gloves, goggles and footwear at all times during handling and application.

Keep out of reach of children. Handle with care and mix only in a closed container. Use only in well ventilated areas. When sanding and removing old antifouling paint, use a face mask to prevent inhalation of sanding dust. When using, do not eat, drink, or smoke. Take a shower immediately after work. Wear freshly laundered clothes daily. Wash hands and face before eating, drinking, smoking and using the toilet. Store and wash all protective clothing separately from household laundry. Wash protective clothing in detergent and hot water before reuse.

**FIRST AID INSTRUCTIONS:** Move to fresh air. If breathing is difficult, administer artificial respiration. Contact physician.  
**SKIN CONTACT:** Remove contaminated clothing. Wash with soap and water. If irritation persists, contact a physician.  
**EYES:** Flush with clean water for 15 minutes. Contact a physician.  
**INGESTION:** Do not induce vomiting. Contact physician immediately.

**TOXICOLOGICAL INFORMATION:** Contains petroleum distillates. Acute overexposure may cause anaesthesia, headache, nausea, narcosis, defatting of skin or eye irritation.

**ENVIRONMENTAL HAZARDS:** Toxic to aquatic organisms. Do not contaminate water. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

**DISPOSAL:** Dispose of empty containers and paint debris in accordance with Provincial requirements. For information on disposal of unused product and cleanup spills, contact the regional office of Environmental Protection, Environment Canada.

"Sellers guarantee shall be limited to the terms set out on this

label and subject thereto, the buyer assumes the risk to persons or property arising from the use or handling of this product and accepts the product on that condition."

Printed by Jesperson Press Limited

\*\*\*\*\*

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))