

97.01.02

WOOLSEY

SEA MATE

50 RED

SKIN IRRITANT

EYE IRRITANT

READ THE LABEL BEFORE USING

FOR USE ON BOATS ONLY

COMMERCIAL

MARINE

GUARANTEE

CUPROUS OXIDE ... 25%  
Copper (as elemental)

REGISTRATION NO. 21639

PEST CONTROL PRODUCTS ACT

DANGER POISON

NET CONTENTS 3.8 LITRES

CAUTION!

KEEP OUT OF REACH OF CHILDREN

FLAMMABLE.

SEE OTHER CAUTIONS ON BACK PANEL.

KOP-COAT, INC.  
WOOLSEY DIVISION  
ROCKAWAY, NJ  
07866  
USA

SEA MATE ANTI-FOULING BOTTOM PAINT

PREPARATION: Wood hulls should be dry, smooth and free from grease or oil. Remove all loose paint and foreign substances. Fill seams with Woolsey 895 Underwater Seam Compound. Metal hulls - Steel: Apply 2/3 coats of Woolsey 652/651 Epoxy Primer, following label directions for these products. Aluminum hulls: Prime with 3 coats of Woolsey 648/649 \*MFP\* Catalyzed Epoxy Primer.

FIBREGLASS: On bare (unpainted) fibreglass, first scour and scrub with Woolsey \*Shipmate\* Heavy Duty Fibreglass cleaner or other strong abrasive agent. Rinse well with fresh water and allow to dry. Sand vigorously until all sheen on \*gel coat\* has been removed. Use 1/0 or No. 80 grit production paper. Wipe with clean rag moistened with paint thinner. Apply one coat of Woolsey 648/649 \*MFP\* Epoxy Primer, using a natural bristly brush. Allow to dry overnight.

APPLICATION: Stir contents thoroughly and mix occasionally during use to keep the high content of toxic pigment in uniform suspension.

THINNING: For first coat on new or bare wood, thin 10% with Woolsey 433 Paint Thinner, turpentine or mineral spirits. For other uses, thinning is normally not required.

COVERAGE: 51 sq. metres per 3.8 litres first coat on new wood. 56 sq. metres per 3.8 litres for second coat or prepaint work.

NUMBER OF COATS: On new or Bare Wood use 3 coats allowing at least 3 hours between applications. On old painted hulls in good condition and on primed metal or primed fibreglass, apply one full coat of this paint followed with a second coat where severe fouling exists as in tropical waters.

LAUNCHING: Allow at least 4 hours and up to one week after final coat before launching. When Epoxy Primer is used, allow 72 hours before launching.

Large vessels (i.e. over 25m) must be treated by trained applicators.

SELLER'S GUARANTEE SHALL BE LIMITED TO THE TERMS SET OUT ON THE LABEL AND, SUBJECT THERETO, THE BUYER ASSUMES THE RISK TO PERSONS OR PROPERTY ARISING FROM THE USE OR HANDLING OF THIS PRODUCT AND ACCEPTS THE PRODUCT ON THAT CONDITION.

KEEP OUT OF REACH OF CHILDREN

Handle with care and mix only in a closed container. Use only in well ventilated areas. When using do not eat, drink or smoke. Take a shower immediately after work. Wear freshly laundered clothes daily. Wash hands and face before eating, drinking, smoking and using the toilet. Store and wash all protective clothing separately from household laundry. Wash protective

clothing in detergent and hot water before reuse.

#### NOTICE TO USER

This control product is to be used only in accordance with the directions on this label. It is an offence under the Pest Control Products Act to use a control product under unsafe conditions.

#### CAUTION

Keep away from heat, sparks and flame. Vapours heavier than air cause health and explosion hazards. Keep containers tightly closed when not in use. Avoid contact with eyes, skin and clothing. Do not breath vapours or spray mist. USE AN AIR-FED RESPIRATOR WITH FULL FACE MASK DURING HANDLING AND APPLYING. WEAR CHEMICAL RESISTANT GLOVES AND FOOTWEAR AND CHEMICAL RESISTANT CLOTHING AT ALL TIMES DURING HANDLING AND APPLYING.

#### FIRST AID

IF SWALLOWED: Drink promptly a large quantity of milk, egg white, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

IF IN EYES: Flush with plenty of water. Get medical attention.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

#### ENVIRONMENTAL HAZARDS

Toxic to aquatic organisms. do not contaminate water. Do not apply directly to water by cleaning equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

#### DISPOSAL

Dispose of empty containers and paint debris in accordance with provincial requirements. For information on the disposal of unused or unwanted product and the cleanup of spills, contact the Provincial Regulatory Agency or the Manufacturer.

#### PHYSICAL OR CHEMICAL HAZARD:

FLAMMABLE! Do not use or store near heat or open flame.

\*\*\*\*\*

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))