

**PRECAUTIONS****Keep out of reach of children****HAZARDS TO HUMANS****DANGER**

Corrosive. Causes irreversible eye damage. Causes skin burns. Harmful if inhaled. May be fatal if swallowed. Harmful if absorbed through skin. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Causes asthmatic signs and symptoms in hyper-reactive individuals. Do not get in eyes, on skin, or clothing. Avoid breathing vapor. Do not swallow. Wear goggles, protective clothing and rubber gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

**FIRST AID**

**IF IN EYES** : Immediately flush with plenty of water for at least 15 minutes. Do not remove contact lenses, if worn. Get immediate medical attention.

**IF ON SKIN** : Immediately wash with plenty of soap and water. Get medical attention.

**IF INHALED** : Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, call a physician.

**IF SWALLOWED** : DO NOT INDUCE VOMITING. Do not give anything to drink. Seek medical advice with urgency or call Poison Control Center.

Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

**TOXICOLOGICAL INFORMATION**

Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory, shock, respiratory depression and convulsion may be needed.

**DISPOSAL**

1. Triple or pressure rinse the empty container. Add the rinsings to the treatment site.
2. Follow provincial instructions for any required additional cleaning of the container prior to its disposal.
3. Make the empty container unsuitable for further use.
4. Dispose of the container in accordance with provincial requirements.
5. For information on the disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill and for clean-up of spills.

**STORAGE AND HANDLING**

**GLUSAN 50** Slimicide solutions are incompatible with many commonly used materials of construction such as steel, galvanized iron, aluminum, tin, and zinc. These solutions can be stored and handled in baked phenolic lined steel polyethylene, stainless steel, or reinforced epoxy-plastic equipment. This product freezes at about – 21°C. Therefore, unless the storage tank is inside or underground, heating and insulation may be required. If heating is needed, exposure to high temperatures should be avoided. For short storage times (up to about 1 month), temperatures of up to 38°C can be tolerated but the preferred maximum storage temperature is about 27°C.

A stainless steel centrifugal pump is suggested for transfer service. Spiral wound stainless steel with TEFLON<sup>®</sup> is suitable for gaskets and packing.

**GLUSAN 50 SLIMICIDE**

**A MICROBIOCIDE CONTROLLING SLIME FORMING BACTERIA, SULFATE REDUCING BACTERIA, FUNGI AND YEAST IN PAPER MILLS PROCESS WATER SYSTEMS AND WATER BASED COATINGS FOR PAPER AND PAPERBOARD.**

**GUARANTEE:**

**Active Ingredient:** Glutaraldehyde.....50.0%

**REGISTRATION NO. 27592****PEST CONTROL PRODUCTS ACT****COMMERCIAL  
DANGER****POISON CORROSIVE****READ THE LABEL BEFORE USING****CONSTANT AMERICA INC.**

2120 CABOT  
MONTREAL, QUEBEC,  
CANADA H4E 1E4

Telephone: 1-800-565-7888

SHIPPING NAME	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (CONTAINS GLUTARALDEHYDE)	
HAZARD CLASS	ID NUMBER	
8	UN 3265	PG II

**T.D.G. PERMIS NO. : SU 5679**

**24 HOUR CHEMICAL EMERGENCY  
SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT  
CALL COLLECT TO CANUTEC AT 613-996-6666**

**NOTICE TO USER**

This control product is to be used only in accordance with the directions on this label. It is an offence under the Pest Control

Products Act to use a control product under unsafe conditions.

**DIRECTIONS FOR USE****PAPER MILLS AND PAPER MILL PROCESS WATER SYSTEMS**

**GLUSAN 50 Slimicide** should be added to the system at a point of uniform mixing such as the head box, beaters, broke chest, save- all tank, or white-water tank.

**Initial Treatment:** When the system is noticeably contaminated, add 0.25 to 1.5 Kg of **GLUSAN 50 Slimicide** per metric tonne of pulp or paper (dry basis) as a slug dose. Repeat until control is achieved. Heavily fouled systems should be boiled out prior to initial treatment.

**Subsequent dose:** When microbial control is evident, add 0.15 to 1.0 Kg of **GLUSAN 50 Slimicide** per metric tonne of pulp or paper (dry basis) as a slug dose as necessary to maintain control.

**WATER-BASED COATINGS, PIGMENTS AND FILLER  
SLURRIES FOR PAPER AND PAPERBOARD**

Add sufficient quantities of **GLUSAN 50 Slimicide** to produce a concentration of 100 to 600 ppm **GLUSAN 50 Slimicide** based on slurry solids.

**NOTICE TO BUYER**

"Seller's guarantee shall be limited to the terms on the label and subject thereto, the buyer assumes risk to persons or property arising from the use or handling of this product and accepts the product on condition."

**BEFORE HANDLING OR USING, READ AND UNDERSTAND  
CURRENT CONSTANT AMERICA MATERIAL SAFETY DATA  
SHEET FOR THIS PRODUCT.**

**Lot No.****Net Contents**

\*\*\*\*\*

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.