

**Matchless** (member paintcafe.com)  
**Boat and Yacht Coating**  
Premium Antifouling Paint /Domestic

**CAUTION- FLAMMABLE DANGER- POISON**

**IMPORTANT :** read the label before using. For use on boat only. Skin and eye irritant. Not for spray use. Only brush or roller application.

Guarantee: Cuprous Oxide 36%, Copper as elemental 30% - Registration No.22572- Pest Control Product Act

**342 BLACK Net Contents 3.78 L**

---

**DIRECTIONS FOR USE**

**SURFACE PREPARATION: Steel surfaces:** Surface must be clean, dry and free of rust. New steel must be primed with an epoxy or anti-corrosive primer 545-061. Apply one or two coats of Antifouling paint. **New wood:** Must be clean and dry. Apply one coat of alkyd primer, let dry for 24 hours. Apply one or two coats of Antifouling paint. **Fiberglass:** Wash the fiberglass and follow with a thorough cleaning of the surface with Chem-Sol 545-153 to remove all wax contaminants, change clothes frequently during this procedure. Sand thoroughly to dull the surface. Remove all sanding dust with thinner, apply fiberglass primer and apply one or two coats of Antifouling. **Painted surface:** Surface must be clean, dry and free of rust and contaminants. Sand if surface is glossy. Spot prime any bare spots. Do not use this product on aluminum hulls and out drives.

**APPLICATION: Mix** only in a closed container. Apply by a brush or roller at a temperature between 10 °C - 30 °C. **Clean up:** Use Chem-Sol 545-153. **Coverage:** 9m<sup>2</sup>/L **Drying time:** Allow 8 hours between coats. **Immersion:** Minimum 12 hours.

**NOTICE TO USERS:** This product is to be used in accordance with the directions on this label. It is an offence under the Pest Control Product Act to use a control product under unsafe conditions. This product is to be used only as an Antifouling paint on underwater surfaces of ships and boats

**PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN** and away from sparks, heat and flames. Vapors from this product are heavier than air and may cause health and explosion hazards. Keep container tightly closed when not in use. Avoid contacts with eyes, skin and clothing. Do not breath vapors. Wear chemical resistant clothing, head covering, gloves, goggles and footwear at all time during handling and application. Handle with care and mix only in a closed container. Use only in well ventilated areas. When sanding and removing old Antifouling paint, use an air-fed respirator with a full-face mask to prevent inhalation of sanding dust. When using do not eat, drink or smoke. Take a shower immediately after work. Wear freshly laundered clothes daily. Wash hand and face before eating, drinking or smoking and using the toilet. Store and wash all protective clothing separately from household laundry. Wash protective clothing in detergent and hot water before reuse.

**FIRST AID INSTRUCTIONS: Inhalation:** Move to fresh air. If necessary, administer artificial respiration. **Eye contact:** Flush with clean water for 15 minutes. **Ingestion:** Do not induce vomiting. **Skin contact:** Remove contaminated clothing; wash well with water and soap. Contact a physician immediately. Take container, label or product name and PCP registration number with you when seeking medical attention. **TOXICOLOGICAL INFORMATION:** Contains petroleum distillates. Acute overexposure may cause: nausea, chills, respiratory irritation, skin

irritation, eyes irritation. **ENVIRONMENTAL HAZARDS:** Toxic to aquatic organisms. Do not clean the equipment directly to water. Do not allow chips or dust generated during paint removal to enter water. **DISPOSAL:** Dispose of empty containers and paint debris in accordance with Provincial requirements. For information on disposal of unused product and clean up of spills, contact the regional office of the environmental protection, Environment Canada.

**SATISFACTION GARANTEED:** If this product is used in accordance with the directions on this label and if you are not satisfied, Laurentide Atlantic Ltd pledges to replace it or reimburse for the cost of this product. Please note: this warranty does not cover any expenses other than product replacement cost.

Notification Change

LAURENTIDE ATLANTIQUE LTEE  
9322 MAIN STREET, PO BOX 368  
RICHIBUCTO, NB E4W 4C7

\*\*\*\*\*

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+) )