

95.05.26

PPG

Pilt Plus
GC-447 Conductive Concentrate
Wood Preservative and Water Repellant with TBTO

Industrial

READ THE LABEL BEFORE USING
KEEP OUT OF THE REACH OF CHILDREN

WARNING
FLAMMABLE
POISON
CORROSIVE

DANGER
CORROSIVE TO EYES
SKIN IRRITANT

GUARANTEE: Bis (tributyl tin) oxide.....3.36%

REGISTRATION NUMBER 19539
PEST CONTROL PRODUCTS ACT

Net Contents 204 L

PPG CANADA INC.
880 AVONHEAD ROAD, MISSISSAUGA
ONTARIO L5J 2Z5

WOOD PRESERVATIVE AND WATER REPELLANT TREATMENT

Recommended Uses: PILT(R) is designed to be used to treat exterior millwork, door and window sash components, outdoor furniture components prior to topcoating and siding for above ground applications. The CMHC (Canada Mortgage and Housing Corporation) recognizes that "PILT(R)" complies with the preservative requirements of CAN 3-A440-M84 CSA Standard for Windows. Each product is specific for conventional or electrostatically applied primers and topcoats. PILT can be used without topcoating. Parts treated with this product are odourless when dry.

Limitations: Do not use for below ground contact applications requiring preservative qualities, or for logs used in construction of log homes. Do not apply where the preservative may become a component of food feed or drinking water. Do not apply as an anti-fouling agent or as a preservative for marine or fresh water structures.

Directions for Use: Blend one (1) part by volume of PILT Concentrate with four (4) parts by volume of Aliphatic Hydrocarbon Reducing solvent. Do not apply undiluted concentrate to wood products. Immerse the wooden parts by either flowcoating, dipping double vacuum or commercial spray box. Allow the part to swell in contact with the PILT a minimum of 15 seconds for flow coater or spray box and 3 minutes for bundle dip. Remove from solution and allow the wood to dry at 65-75 F (18-24 C) in an area with engineered ventilation to remove vapours. All equipment must be free of leaks with provision to eliminate or contain over spray, drips and spillage.

Dry Time: Bundle Dipping - Min. 72 hrs Large Single Units - Min. 24 hrs. Small Single Units - 2 hrs. or shorter (depending on equipment used by flow coater - 5 minutes).

Double Vacuum Treatment: The treating schedule used must insure that the wood is dry to touch upon removal from the treating vessel.

Surface Preparation: Must be applied to unpainted, clean, dry wood.

Technical Service: For technical service call PPG Canada Inc., Coatings & Resins Group, 880 Avonhead Road, Mississauga, Ontario, L5J 2Z5, (416) 823-1100.

CAUTIONS:

Post a copy of this Label in the work area. Wear protective clothing, coveralls, boots, rubber gloves and aprons when applying, mixing and handling freshly treated wooden parts or structures. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Operators and individuals who enter, clean, repair or weld tank must wear a respirator. Applicators must not eat, drink or use tobacco while working with treatment formulations. Wear eye protection when handling or diluting concentrate. Avoid skin contact. Wash protective clothing separately from household items. Flammable. Keep away from heat and open flame. Protective clothing must be changes when is shows signs of contamination. Leave all protective clothing at the plant. Do not get on skin or in eyes. Wear eye protection when handling concentrates. May be fatal if swallowed or inhaled. Avoid breathing vapours or spray mist. Use only in a well ventilated area.

Environmental Hazards:

This product is toxic to fish and wildlife. Do not apply directly to water or wet lands. Do not contaminate water by cleaning equipment or disposal of waste.

DISPOSAL:

Do not contaminate water, food, or feed by storage or disposal.

1. Rinse the emptied container thoroughly and add the rinsings to treatment site.
2. Follow provincial instructions for any required additional cleaning of the container prior to its disposal or reconditioning.
3. Dispose of the container in accordance with provincial requirements.
4. For information on the disposal of unused, unwanted product and the cleanup of spills contact the regional office of Environment Canada.
5. For small spills. Recover free liquid. Soak up residue with solids absorbent. DO NOT FLUSH INTO SURFACE STREAMS. INFORM ENVIRONMENT CANADA AS IN #4.

Clean Up: Use Aliphatic Hydrocarbon solvent for clean-up.

FIRST AID:

In case of skin contact, remove contaminated clothing and immediately wash skin with soap and water. Get medical attention. Wash contaminated clothing before reuse. If in eyes, flush eyes with water for at least 15 minutes. Get medical attention. If swallowed, do not induce vomiting. Get immediate medical attention. If inhaled, remove to fresh air. Use artificial respiration if breathing has stopped. Get immediate medical attention. Contains Petroleum Distillates.

TOXICOLOGICAL INFORMATION:

Contains petroleum distillates. Medical Response Information: Emergency medical or spill control information (304) 843-1300.

NOTICE TO BUYER:

Seller's guarantee shall be limited to the terms set out on the label and subject thereto, the buyer assumes the risk to persons or property arising from the use or handling of this product and accepts the product on that condition.

NOTICE TO USER:

This control product is to be used only in accordance with

thedirections on this label. It is an offence under the Pest Control Products Act to use a control product under unsafe conditions.

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))