

94.12.29

SIGMA COATINGS

5297 BR SIGMAPLANE ECOL  
ANTIFOULING PAINT

BROWN

COMMERCIAL

GUARANTEE:

Cuprous oxide.....43.2%  
Copper (as elemental).....38.4%

READ THE LABEL AND PRODUCT DATA SHEET  
BEFORE USING

FLAMMABLE LIQUID SKIN AND EYE IRRITANT

DANGER

POISON

REGISTRATION No. 23154  
PEST CONTROL PRODUCTS ACT

NET CONTENTS 18.9 LITRES

SIGMA COATINGS  
1401 Destrehan Ave  
Harvey, LA 70058

PRECAUTIONS:

Wear an air-fed respirator with a full face mask during handling and application. Wear chemical resistant gloves and footwear and chemical resistant clothing with head covering at all times during handling and application.

Keep out of reach of children.

Handle with care and mix only in a closed container.  
Use only in well ventilated areas. When using do not eat, drink or smoke.  
Take a shower immediately after work.  
Wear freshly laundered clothes daily.  
Wash hands and face before eating, drinking, smoking and using the toilet.  
Store and wash all protective clothing in detergent and hot water before reuse.

#### FIRST AID:

If splashed in eyes or on skin, flush thoroughly with water for 15 minutes. For eye contact, get medical attention. If swallowed, drink 2 or 3 glasses of milk or water. Do not induce vomiting. Call a physician immediately.

#### TOXICOLOGICAL INFORMATION

Contains petroleum distillates. Do not induce vomiting.

Corrosive. Causes irreversible eye damage. Harmful if absorbed through skin. Due to corrosive nature, may be harmful or fatal if swallowed. Avoid contact with skin, eyes and clothing.

#### NOTICE TO USER:

This control product is to be used only in accordance with the directions on this label. It is an offense under the Pest Control Products Act to use a control product under unsafe conditions.

#### ENVIRONMENTAL HAZARDS

Toxic to aquatic organisms. Do not contaminate water. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

#### DISPOSAL

Dispose of empty containers and paint debris in accordance with provincial requirements. For information on the disposal of unused or unwanted product and the cleanup of spills, contact the regional office of Environment Canada.

#### DIRECTIONS FOR USE

General Directions: For use on metal and fiberglass boat hulls to control barnacle growth in fresh and salt water. Do not apply below (36 degrees F) 3 degrees C unless care is taken to insure absence of frost or ice. Surfaces to be painted shall be free of dirt, oil, grease and other surface contaminants. Apply in

accordance with Sigma's directions or specifications given in the Technical Data Sheet for 5297. For steel surfaces, use only the primer recommended in the Technical Data Sheet.

The minimum drying time before introduction into water is 8 hours.

Large vessels, that is vessels over 25 meters, must be treated by trained applicators.

Read the product data sheet for 5297 Sigmaplane Ecol

\*\*\*\*\*

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))