

96.04.22

KOP-COAT

WOODLIFE (R) - P
CLEAR WOOD PRESERVATIVE
WITH WATER REPELLENT

FOR INDUSTRIAL USE ONLY

GUARANTEE:

Propiconazole: 1-[2-(2,4-dichlorophenyl)-4-propyl-1,3-
dioxolan-2-yl-methyl]-1H-1,2,4-triazole 0.50%

READ THE LABEL BEFORE USING

KEEP OUT OF REACH OF CHILDREN

CAUTION SKIN IRRITANT

REGISTRATION NO. 24136

PEST CONTROL PRODUCTS ACT

KOP-COAT, INC.
Protection Products Division
436 Seventh Avenue
Pittsburgh, PA 15219

5137 Southwest Avenue
St. Louis, MO 63110

(412) 227-2700

NET CONTENTS: LITRES

DIRECTIONS FOR USE

DO NOT DILUTE

USES: For wood joinery products including window and door components or exterior non-structural decorative wood joinery items which are not in ground contact. Do not use on wood products which may come in contact with food, feed, or drinking water. Machine, cut glue and sand wood as desired prior to treating. Do not apply over previously finished or stained wood. Wood must be clean and dry. Apply at temperatures above 4.4°C and below 25°C. Engineered ventilation systems may be required

to remove solvent vapours during treatment, mixing and drying.

USE LIMITATION: Treatment facilities shall provide appropriate industrial hygiene measures and safety equipment for the safe use of this product. The treatment site must have effective containment and pollution abatement technology to insure that the pesticide is not released into the surrounding environment under normal operating conditions. Freshly treated wood shall be handled and stored in a manner which provides no opportunity for the preservative release into the environment. Outdoor treatment facilities are prohibited.

APPLICATION:

1. Double vacuum system (closed systems). Wood should be dry to the touch upon removal from the treating chamber. Use a treating schedule which achieves adequate distribution of propiconazole to meet market standards or customer specifications;
2. Bundle dipping or other immersion methods which utilizes automated technology (3 minute minimum treatment).
3. Flood coating, roller coating or flow coating using automated technology (15 second minimum treatment).
4. Spray box automated technology (treating parameters appropriate for the specific unit and substrate).

FINISHING: Prior to top-coating with paint, varnish, or other materials, the wood must be free of residual solvent. Allow four to eight hours under ambient temperature, 20°C or less drying time if accelerated drying methods are used.

STORAGE: Store in the original closed and labelled container in a cool place. Keep containers closed when not in use. Store at above 0°C.

DISPOSAL:

1. Rinse the emptied container thoroughly and add the rinsings to the treatment site.
2. Follow provincial instructions for any required additional cleaning of the container prior to its disposal.
3. Make the empty container unsuitable for further use.
4. Dispose of the container in accordance with provincial requirements.
5. For information on the disposal of unused, unwanted product and the cleanup of spills, contact the Provincial Regulatory Agency or the Manufacturer.

CLEAN UP: Use mineral spirits to remove wood preservative from contaminated surfaces.

PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN

POST A COPY OF THIS LABEL IN THE WORK AREA

May cause eye and skin irritation. Avoid breathing of vapour or spray mist. Avoid contact with skin, eyes and clothing.

When working in the treatment areas or when handling/cleaning contaminated equipment, wear coveralls, full face protection with cartridge respirator, and impermeable gloves. In addition, wear apron and boots if there is a potential for getting wet by the preservative solution.

When handling freshly treated lumber, wear long pants and long-sleeved shirts and impermeable gloves. Wear impermeable apron and boots if there is a potential for getting wet by the preservative solution. Once dry, the treated wood can be handled with cotton and leather gloves.

Wash hands and face thoroughly with soap and water after handling and before eating, drinking, smoking and using the toilet. Change clothing daily or more frequently if it shows signs of contamination. Wash contaminated clothing separately from household laundry. Not for use or storage in or around the home. Clean contaminated equipment thoroughly prior to making welding repairs.

FIRST AID:

If Swallowed: Do not induce vomiting. Promptly drink a large quantity of milk, egg whites or gelatin solution. If these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

If On Skin: Wash with plenty of soap and water. Get medical attention if irritation persists.

If In Eyes: Flush with plenty of water. Get medical attention.

If Inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Call a physician.

TOXICOLOGICAL INFORMATION: No specific antidote known. Treat symptomatically. Contains mineral spirits.

PHYSICAL AND CHEMICAL HAZARDS: Do not use or store near heat or open flame. In case of fire, use water spray, foam, carbon dioxide or dry chemical. Keep from freezing. Store above 0°C.

ENVIRONMENTAL HAZARDS: This product is toxic to fish. Do not apply directly to any body of water. Do not contaminate water by cleaning of equipment or when disposing of equipment washwaters.

NOTICE TO BUYER:

Seller's guarantee shall be limited to the terms set out on the label and subject thereto. The buyer assumes the risk to persons or property arising from the use or handling of this product and accepts the product on that condition.

NOTICE TO USER:

This control product is to be used only in accordance with the directions on this label. It is an offence under the Pest Control Products Act to use a control product under unsafe conditions.

FOR PRODUCT EMERGENCIES: 1-800-548-0489

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))