

98.01.19

PENTOX(R)

Primer Sealer

Wood Preservative

Brown

INDUSTRIAL USE ONLY

Guarantee:

Propiconazole: 1-[2-(2,4-dichlorophenyl)-4-propyl-1,3-dioxolan-2-y)-methyl]-1H-1,2,4-triazole ..... 1.47% (by wt.)

READ THE LABEL BEFORE USING

KEEP OUT OF REACH OF CHILDREN

CAUTION

POISON

SKIN & EYE IRRITANT

SKIN SENSITIZER

REGISTRATION NO. 24137

PEST CONTROL PRODUCTS ACT

20 l

or

205 l

OSMOSE-PENTOX INC.

1080 PRATT, MONTREAL, QUEBEC, H2V 2V2

CANADA

PENTOX Primer Sealer Wood Preservative Brown is used for the preservation of clean dry wood against blue stains and rot fungi. Use it to control warping and checking. It is an ideal primer-sealer wood preserver. The treated wood can be stained, painted, or varnished with conventional exterior and interior finishes. It extends the life of the finish and the wood. Meets Canadian Standard Association and National Woodwork

## Manufacturers Specifications.

### USE LIMITATION:

Treatment facilities shall provide appropriate industrial hygiene measures and safety equipment for the safe use of this product. The treatment site must have effective containment and pollution abatement technology to ensure that the preservative is not released into the surrounding environment under normal operating conditions. Freshly treated wood shall be handled and stored in a manner which provides no opportunity for the preservative's release into the environment. Outdoor treatment facilities are prohibited.

### DIRECTIONS FOR USE:

Post a copy of this label in the treatment area. Dilute this product with a suitable mineral spirit solvent, to provide a working solution concentration of between 0.5% and 1.0% propiconazole (eg., 1 part preservative to 1 part solvent) for the protection of wood against decay and molds.

For use on wood joinery products including window and door components or exterior non-structural decorative wood joinery items which are not in ground contact. Do not use on wood which may come in contact with food, feed, or drinking water. Machine, cut, glue and sand wood as desired, prior to treating. Do not apply over finished or stained wood. Wood must be clean and dry. Apply at temperatures above 5°C. Engineered ventilation systems may be required to remove solvent vapours during treatment, mixing, or drying.

Apply this product by the following methods:

- a) Double vacuum system (closed system). Wood should be dry to the touch upon removal from the treating chamber. Use a treating schedule which achieves adequate distribution of preservative to meet market standards or customer specifications.
- b) Bundle dipping or other immersion methods which utilize automated technology. (3 minute minimum treatment)
- c) Flood coating, roller coating, or flow coating, using automated technology. (15 second minimum treatment)
- d) Spray box automated technology. (treating parameters appropriate for the specific unit and substrate)

Finishing:

Prior to top-coating with stain, paint, varnish or other materials, the wood must be free of residual solvent. Allow four to eight hours under ambient temperature, 20°C; or less drying time if accelerated drying methods are used.

Clean up:

Use mineral spirits to remove wood preservative from contaminated surfaces.

Disposal:

1. Rinse the emptied container thoroughly with mineral spirits and add the rinsings to treatment site.
2. Follow provincial instructions for any required additional cleaning of the container prior to its disposal.
3. Make empty container unsuitable for further use.
4. Dispose of the container in accordance with provincial requirements.
5. For information on the disposal of unused, unwanted product, and the clean up of spills, contact the Provincial Regulatory Agency or Manufacturer.

Storage:

Store in the original closed and labelled container in a cool place. Keep containers closed when not in use. Store above 0°C.

#### PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN. POST A COPY OF THIS LABEL IN THE WORK AREA. Potential skin sensitizer. Harmful if swallowed, inhaled, or absorbed through the skin. May cause eye and skin irritation. Avoid breathing of vapor or spray mist. Avoid contact with skin, eyes, and clothing. Use only in well ventilated areas. When handling the concentrate, (or when working in the treatment area or when handling/cleaning contaminated equipment and there is the possibility of getting wet by preservative solution) wear coveralls, full face protection with cartridge respirator and impermeable gloves, aprons and boots.

When handling freshly treated lumber, wear long pants and long-sleeved shirts and impermeable gloves. Wear impermeable apron and boots if there is a potential for getting wet by the preservative solution. Once dry, the treated wood can be handled with cotton and leather gloves.

Wash hands and face thoroughly with soap and water after handling and before eating, drinking, smoking, and using the toilet. Change clothing daily or more frequently if it shows signs of contamination. Wash contaminated clothing separately from household laundry. Not for use or storage in or around the home. Clean contaminated equipment thoroughly prior to making welding repairs.

#### FIRST AID:

If Swallowed: Do not induce vomiting. Promptly drink a large quantity of milk, egg whites or gelatin solution. If these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

If On Skin: Wash with plenty of soap and water. Get medical attention if irritation occurs and persists.

If In Eyes: Flush with plenty of water. Get medical attention.

If Inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Call a physician.

#### TOXICOLOGICAL INFORMATION:

Contains mineral spirits. No specific antidote known. Treat symptomatically.

#### PHYSICAL AND CHEMICAL HAZARDS:

Do not use or store near heat or open flame. In case of fire, use water spray, foam, carbon dioxide or dry chemical.

#### ENVIRONMENTAL HAZARDS:

This product is toxic to fish. Do not apply directly to any body of water. Do not contaminate water by cleaning of equipment or when disposing of equipment wash waters.

#### NOTICE TO BUYER:

Seller's guarantee shall be limited to the terms set out on the label and subject thereto. The buyer assumes the risk to persons or property arising from the use or handling of this product and accepts the product on that condition.

#### NOTICE TO USER:

This control product is to be used only in accordance with the

directions on the label. It is an offence under the Pest Control Products Act to use a control product under unsafe conditions.

(C) Osmose Pentox Inc. 1996

\*\*\*\*\*

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))