

90.04.04

BETZ

C-5P

MICRO-ORGANISM CONTROL AGENT

INDUSTRIAL

CAUTION          POISON  
CAUTION          CORROSIVE

READ THE LABEL BEFORE USING

GUARANTEE:

1,3-dichloro-5, 5-dimethylhydantoin ..... 48%

REGISTRATION NO. 13481  
PEST CONTROL PRODUCTS ACT

NET WEIGHT AS MARKED ON CONTAINER

CONTENTS: PELLETS

C-5P

AGENT DE CONTROLE DE MICRO-ORGANISMES

A USAGE INDUSTRIEL

ATTENTION          POISON  
ATTENTION          CORROSIVE

GARANTIE:

1,3-dichloro-5, 5-dimethylhydantoin ..... 48%

NO. D'ENREGISTREMENT 13481  
LOI DES PRODUITS PESTICIDES

POIDS NET TEL QU'INDIQUE SUR LE CONTENANT

BETZ INC.  
3026 Solandt Road  
Kanata, Ontario  
K2K 2A5

PRECAUTIONS: HARMFUL IF SWALLOWED. Keep material dry. If material gets wet, it may decompose, liberating toxic chlorine gas. Avoid inhalation. Causes skin irritations. Do not get into eyes, on skin or clothing. Wear rubber gloves, and goggles or face shield, when handling.

FIRST AID: In case of contact with skin, wash well with soap and water. In case of contact with eyes, flush promptly and thoroughly with water. In case on ingestion or contact with eyes or inhalation of chlorine gas, secure immediate medical attention.

Do not reuse empty container. Send to drum reconditioner, or destroy by perforating or crushing and bury in a safe place.

#### DESCRIPTION AND USE

Betz C-5P aids in the control of fungi and bacteria in the water in brewery pasteurizers, in recirculating industrial water cooling towers, and in pulp and paper mill process water. In the case of brewery pasteurizers, this product should be used at a rate of 10- 75g/kL of water per compartment.

In recirculating cooling tower systems and pulp and paper mill process water, use at rate of 20-100g/10,000 (Kl) of water contained in the system.

Begin treatment when the system is in jeopardy of becoming affected or after cleaning systems whose efficiency is already impaired. Apply at a point in the system where the product will be uniformly mixed. Repeat treatment every day, or as needed. In the event the system is badly fouled, precleaning is recommended.

Measurement of the residual chlorine levels in the systems should be made on a periodic basis to insure a 0.2 to 0.5 part per million (ppm) residual minimum.

FOR INDUSTRIAL USE ONLY: Technical advice regarding specific site

problems is available from BETZ.

NOTICE TO USER: This control product is to be used only in accordance with the directions on this label. It is an offense under the Pest Control Products Act to use a control product under unsafe conditions.

KEEP IN COOL DRY PLACE - KEEP CONTAINER COVERED

\*\*\*\*\*

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))